

The technical scheme do not consider the dimensions of any postural and anti decubitus cushions.

SW: Considered external tube to external tube of the frame. The dimension between the internal faces of the side guards is +10 mm than the SW. BRH: Considered from the seat (upholstery or carbon) to the top of the backrest tube.

SD: Considered as the depth of the seat. The seat plate can be slided of 20 mm (only in case of carbon CARBTS or CARBFS).

CG: Considered from the backrest tube to the axle of the rear wheels. FD: Frame Depth = StF + SD - 10mm + 120mm

SHF and SHR: Seat height front and rear can be adjusted only by tilting the seat. The frame tubes height than the floor is fixed.

For a right sizing of the wheelchair is recommended:

1) SW | Seat Width _ A space of \pm 5 mm between the user basin and the side guards

2 SD | Seat Depth _ A space of ± 50 mm between the user's popliteal fossa and the seat (rigid carbon or upholstery).

SD: 360 - 460 mm

KHL: 310 - 420 mm

in increments

of 10 mm

in increments

of 20 mm



SW: 340 – 440 mm in increments of 20 mm



SHF: 470 – 480 mm (490-520 with the carb. seat / tilting system)







TRASPORT WEIGHT: (Without rear wheels) ± 3.9 kg*



100 Kg

MAXIMUM USER WEIGHT:



BRH: 240 – 405 mm in increments of 15 mm

CG: 100 - 140 mm

TOTAL WIDTH (TW)

(Camber 0°) SW +175 mm (Camber 3°) SW + 220 mm

in increments

of 20 mm



SHR: 400 – 410 mm (410-440 with the carbon seat / tilting system)



BRA: 86° - 90° - 94° - 98° adjustable



TOTAL DEPTH (TD) StF + SD + 120 + 100 + (100-CG)



* CONFIGURATION: SW340 / SD420 / STF120 / CG100 / IMB0TT34 / BKRUR / BRH255 / FOOTFU / BRKASL / CARB.U3 / CARB72 / FRKDS2 / FRWC4 / CARB3 / BKRTT



VAT IT 12848301003 | tel.+39 0444701414 www.ariawheels.com | info@ariawheels.com

Speciale STANDARD CONFIGURATION

2023 rev1

Frame type: Seat width (SW): Seat depth (SD) Seat to footrest (STF): **Camber Rear Wheels (CRW):** Center of Gravity (CG): Seat type: Seat height rear (SHR): Seat height front (SHF): Knee to heel length (KHL): **Backrest system: Backrest height (BRH):** Backrest angle (BRA): Footrest: **Brakes support: Brakes:** Frame color: Rear wheels dimensions: Rear wheels type: Handrim 24" / 25": Pneumatico 24x1.00 / 25x1.00: Forks: Front casters: Side guards support:

Side guards support: Side guards: Backrest: Push handles: Under seat bag / Handle: Calf band:

Manufacturer's suggested retail price: 4300 €

Mono tube frame (MTUBE) from 340 to 440 mm from 360 to 460 mm from 120 to 140 mm 0° or 3° from 100 to 140 mm Adjustable tension upholstery seat (CARBTT) 400 or 410 mm 470 or 480 mm from 310 to 420 mm Fixed backrest (BKRUR) from 255 to 405 mm 90° to floor (BRA90) Black painted welded tubes (FOOTFU) Aluminium standard clamp (BRKASL2) Aria® scissor lock (BRKASL + BRKASR) Metallic grey (GM) 24 " 25 " Black Wheel with black hub and black spokes (RWHAG - RWHAG1) Black anodized aluminium (HDRMB - HDRMB1) Silver anodized aluminium (HDRMS - HDRMS1) Schwalbe Right Run - Black/Grey (WTSWR - WTSWR1) Aria® Double - Sided - black anodized aluminium (FRKDS2) 3" Black anodized aluminium caster (FRWH3) 4" Black anodized aluminium caster (FRWH4) Aluminium support (ALCMT72) Carbon Fiber Rigid (CARB3) Aria® tension straps backrest (BKRTT) None None Calf band, height 8 cm - black textile (CLFB8)